



torbocar AC30



torbocar AC30 - the all-in-one

The torbocar models AC30 to AC76 with assembled torbo-unit plus compressor, plus large water tank, plus hose reel guarantee shortest set-up times and convincing handling.

The torbocar AC30 with torbo S080 or S120 cleans even sensitive surfaces thoroughly, leaving behind shining results even when other blast cleaning machines would have long given up.

While others are still setting up and connecting components, you and your torbocar are already in operation and then on your way home when others are still breaking down.

Technical data:

Volume of vessel	80 (120) l / 2,83 (4,24) Cu. ft.
Volume of water tank	250 l / 66 gal. (Am.)
Hose-reel	40 m / 131 ft. (with 1 Inch hose)
Compressor	3,0 m ³ /min / 106 Cu. ft. per min.
Consumption of blast media (min.-max.)	14,4 - 144 (288) l/h 3,8 - 38 (76) gal (Am.) per h
Consumption of water (min. - max.)	3,6 - 36 (72) l/h 0,95 - 9,5 (19) gal (Am.) per h
Compressor connection (min. - max.)	2 - 5,0 m ³ /min / 4 - 10 bar / 25 mm 70 - 175 Cu. ft. per min / 58 - 145 PSI / 1 Inch
Water connection (min. - max.)	0 - 12 bar 0 - 170 PSI
Connection blast hose	25 mm / 1 Inch
Stream connection	12 Volt / 3 Watt
Dimensions HxWxL, approx.	1.750 x 4.080 x 1.790 mm 68,9 x 160,6 x 70,5 Inch
Weight (empty), approx.	1.220 - 1.320 kg / 2.712 - 2.933 lbs.
Permissible total weight (max.)	1.400 - 2.000 kg / 3.100 - 4.440 lbs.