



# torbo N-LOC 80

## torbo N-LOC 80 – the compact system

The cleaning of facades and monuments as well as the removal of graffiti are only generic terms for the scope of application of the torbo N-LOC.

Very simple operation, low weight and integrated water tank make the torbo N-LOC the ideal standard for municipalities/towns and for rental. The aluminium frame with wheels and retractable handles protects the technical devices from damage and is light to transport.

### Technical data:

Volume of vessel	80 l / 2,83 Cu. ft.
Volume of water tank	40 l / 1,42 Cu. ft.
Hose-reel	---
Compressor	---
Consumption of blast media (min.-max.)	14,4 - 144 l/h 3,8 - 38 gal (Am.) per h
Consumption of water (min. - max.)	3,6 - 36 l/h 0,95 - 9,5 gal (Am.) per h
Compressor connection (min. - max.)	1,5 - 4,0 m <sup>3</sup> /min / 4 - 8 bar / 19 mm 53 - 140 Cu. ft. per min / 58 - 116 PSI / 3/4 Inch
Water connection (min. - max.)	0 - 10 bar 0 - 145 PSI
Connection blast hose	19 mm / 3/4 Inch
Stream connection	12 Volt / 3 Watt
Dimensions	800 x 600 x 1.050 mm
HxWxL, approx.	31,4 x 23,6 x 41,3 Inch
Weight (empty), approx.	130 kg / 287 lbs.
Permissible total weight (max.)	500 kg / 1.100 lbs.